DL5 LED DOWNLIGHT

Easy installation



FEATURES:

- Comes with white bezel as standard others available.
- Easy to install with 55mm cutout •
- Easily switch bezels after installation •
- 1 colour downlight 3 colour options available; 3000K, • 4000K, 6000K

APPLICATIONS

















BATH & SHOWER COMMERCIAL

HOME & RESIDENTIAL

LOBBIES & CORRIDORS OFFICES

5N

RETAIL

5W

DL5 LED DOWNLIGHT

Easy installation

Part No. Part No. Emergency Version DESCRIPTION	230007 230007E 5W DL5 Downlight	230041 230041E 5W DL5 Downlight	230011 230011E 5W DL5 Downlight
COLOUR TEMPERATURE	3000K (Warm White)	4000K (Cool White)	6000K (Daylight)
LUMENS	598lm	680lm	635lm
DIMENSIONS	80mmØ x 51mm depth		
CUTOUT	55mm Ø		
COLOUR RENDITION (CRI)	Ra>80		
BEAM ANGLE	40°		
POWER CONSUMPTION	5kWh/1000hrs		
POWER FACTOR	0.85		
WORKING TEMPERATURES	-30°C to +40°C		
CONSTRUCTION	Aluminum / Plastic IP65 (Bezel only)		
IP RATING	IP65 Bezel Only		
FIRE RESISTANT	BS476-21 30/60/90mins		
CERTIFICATION	CE, RoHS		
ENERGY CONSUMPTION (EC)	5kWh/1000hrs		
WARRANTY	1 year (+ 2 years extended warranty with online registration)		

10mm minimum void space 52mm 52mm 55mm Cut Out

BRIGHT SOURCE

