

# LED FLOODLIGHT

100W

Includes 1m lead wire



IP65  
RATED



1M  
LEAD WIRE



LOW GLARE  
GLASS



PHOTOCELL  
VERSION  
AVAILABLE

## FEATURES:

- High quality
- Robust and durable
- Mounting bracket with adjustable tilt
- Energy saving

**3  
YEAR  
WARRANTY**  
WITH ONLINE  
REGISTRATION

## APPLICATIONS



COMMERCIAL



OUTDOOR



WAREHOUSE  
& STORAGE AISLES



WORK SITES

100W

# LED FLOODLIGHT

Includes 1m lead wire

Part No.

DESCRIPTION

253082

100W 6000K single colour **without** photocell

253099

100W 6000K single colour **with** photocell

DIMENSIONS

380mm x 330mm x 110mm

BODY COLOUR

Black

POWER CONSUMPTION

100W

INPUT VOLTAGE

AC 220V-240V

COLOUR TEMPERATURE

6000K

COLOUR RENDITION (CRI)

Ra >80

LUMEN OUTPUT

10,000lm

IP RATING

IP65

BEAM ANGLE

120°

CONSTRUCTION

Aluminium & Glass

WORKING TEMPERATURE

- 20°C to + 40°C

LIFETIME HOURS

25,000

SWITCH CYCLES

15,000

WARRANTY

1 year (+ 2 year extended warranty with online registration)

CERTIFICATION

UKCA & CE & ERP

EFFICACY RATING


100lm/W



BRIGHT SOURCE



**BRIGHT SOURCE**  
100W LED FLOODLIGHT



**100**  
kWh/1000h



2021 No. 1093