

LED FLOODLIGHT

150W

Includes 1m lead wire



IP65
RATED



1M
LEAD WIRE



LOW GLARE
GLASS



PHOTOCELL
VERSION
AVAILABLE

FEATURES:

- High quality
- Robust and durable
- Mounting bracket with adjustable tilt
- Energy saving

**3
YEAR**
WARRANTY

WITH ONLINE
REGISTRATION

APPLICATIONS



COMMERCIAL



OUTDOOR



WAREHOUSE
& STORAGE AISLES



WORK SITES

150W

LED FLOODLIGHT

Includes 1m lead wire


Part No.	253105	253112
DESCRIPTION	150W 6000K single colour without photocell	150W 6000K single colour with photocell
DIMENSIONS	380mm x 330mm x 110mm	
BODY COLOUR	Black	
POWER CONSUMPTION	150W	
INPUT VOLTAGE	AC 220V-240V	
COLOUR TEMPERATURE	6000K	
COLOUR RENDITION (CRI)	Ra >80	
LUMEN OUTPUT	15,000lm	
IP RATING	IP65	
BEAM ANGLE	120°	
CONSTRUCTION	Aluminium & Glass	
WORKING TEMPERATURE	- 20°C to + 40°C	
LIFETIME HOURS	25,000	
SWITCH CYCLES	15,000	
WARRANTY	1 year (+ 2 year extended warranty with online registration)	
CERTIFICATION	UKCA & CE & ERP	
EFFICACY RATING	100lm/W	



BRIGHT SOURCE



BRIGHT SOURCE
150W LED FLOODLIGHT



150
kWh/1000h



2021 No. 1093