ALL IN ONE LED DOWNLIGHT

New All in One Downlight with Easy-fit Plug'n'Play Connector

Energy efficient LED illumination for all settings with driver on a flexible connection, great for tight spaces.



Bezel Included as Standard White

4 additional bezel finishes are available to purchase separately:



ANTIOUE BRASS [230700]





POLISHED CHROME BRUSHED CHROME [230694]



WITH ONLINE REGISTRATIO

6 Impressive Features, **1 Amazing Downlight**

- **1.** Dimmable
- **2.** Fire-Resistant 30/60/90 minutes
- 3. 3-hour emergency version available
- 4. IP65 Rated with Bezel
- 5. Switchable Wattage 5W-8W
- **6.** 4 Colour Temperatures

FEATURES:

- New 5W/8W downlight added to the range
- Plug'n'Play as standard .
- 4CCT colour temperature changing switch (2700K, 3000K, 4000K, 6000K)
- Bezel included as standard White
- Easy to install
- Switch the bezels after installation
- Trusted, stylish design from the All in One range which includes the 8W/10W fire-rated downlight • and the Tilt 8W/10W

APPLICATIONS



COMMERCIAL

HOMF & RESIDENTIAL


5V

ALL IN ONE LED DOWNLIGHT

New insulation cover with easy fit Plug'n'Play connector

Part No.	230670		
DESCRIPTION	5W/8W All in One Downlight 4CCT		
DIMENSIONS	90 x 45 x 45mm (Excluding driver)		
CUT OUT	65mm diameter		
POWER CONSUMPTION	5W or 8W Selectable		
POWER FACTOR	0.9		
COLOUR TEMPERATURE	2700K (Extra Warm White) / 3000K (Warm White) / 4000K (Cool White) / 6000K (Daylight White)		
COLOUR RENDITION (CRI)	Ra >80		
LUMINENCE FLUX	460-540lm (5W), 720-840lm (8W)		
IP RATING	IP65 (with Bezel only)		
CONSTRUCTION	Aluminum / Polycarbonate		
FIRE RESISTANT	BS476-21 30/60/90 minutes		
BEAM ANGLE	60°		
DIMMABLE	Yes		
LIFETIME	54,000hrs		
WORKING TEMPERATURES	-25°C to +45°C		
CERTIFICATION	CE, UKCA, RoHS		
WARRANTY	1 year (+ 4 years extended warranty with online registration)		
EFFICACY RATING	100lm/W		

Space Requirements



all settings with a driver on a flexible connection, great for tight spaces!



ENERG[†] **Bright Source** 230670



E

8 kWh/1000h



EXCELLENT PERFORMANCE FROM THE **ALL IN ONE** RANGE



8W/10W Switch

230465



8W/10W Switch Tilt 230489

<2700 K	2700	- 3300 K	3300 - 5300 K	>5300 K	
2700k		3000k	4000k	6000k	
Extra Warm \	Nhite	Warm White	Cool White	Daylight	
COLOUR TEMPERATURE SCALE					



BRIGHT SOURCE