LED SLIM WALL PACK



Photocell option available



FEATURES:

- Colour switchable 3000K/4000K/6000K
- Photocell sensor to tailor the light to the environment
- Lightweight slim profile 310 (h)*265 (w)*122 (l)
- High impact polycarbonate lens, perfect to prevent against damage
- Robust die-cast aluminium body
- Top IK (impact) rating of IK10
- Energy saving LED savings of up to 65%
- Resistant to cold and heat from -30°C to +35°C
- IP65 rating
- Replaces 70W SON wall pack

APPLICATIONS



COMMERCIAL



RESIDENTIAL

WAREHOUSE





LED SLIM WALL PACK

Photocell option available

Part No.	243083		243076	
DESCRIPTION	30W LED Slim Wall Pack. Black box with opal diffuser and photocell sensor for outdoor use.		30W LED Slim Wall Pack. Black box with opal diffuser and Comes without photocell sensor	
DIMENSIONS (L-W-D)	310 x 265 x 122mm			
POWER INPUT	220-240V AC			
COLOUR TEMPERATURE	3000K (Warm White)	4000K (Co	ool White)	6000K (Daylight White)
COLOUR RENDITION (CRI)	Ra>80			
LUMENS	2200lm			
COLOUR RENDITION (CRI)	Ra>80			
IP RATING	IP65			
IK RATING	IK10			
CONSTRUCTION	Die-cast aluminium/Polycarbonate			
WORKING TEMPERATURES	-30°C to +35°C			
LIFETIME	50,000 Hours			
SWITCHING CYCLES	50,000			
ENERGY CONSUMPTION	30kWh			
LIFETIME	50,000 hours			
CERTIFICATION	CE, RoHS			
WARRANTY	1 year (+ 4 years extended warranty with online registration)			



BRIGHT SOURCE







Formerly rated A+ (same quality, new energy rating label regulations)

