

LED PANEL

1200 X 300mm

40W

Fits in suspended ceiling grid. Direct replacement for fluorescent luminaires. Installs in minutes!



Emergency Version Available



FEATURES:

- Low maintenance, long-life and eco-friendly design
- Save up to 60% on energy costs over fluorescent
- High-quality light
- Good colour rendition
- No flickering, no UV, no IR
- Direct replacement for fluorescent luminaires
- Installs in minutes
- In-house testing conducted to ensure quality and reliability

APPLICATIONS



EDUCATION



COMMERCIAL KITCHENS



OFFICES



RETAIL

40W

LED PANEL


1200 X 300mm

Fits in suspended ceiling grid. Direct replacement for fluorescent luminaires. Installs in minutes!

Part No.	223092	223108	223115
DESCRIPTION	LED Panel 40W White Frame 3000K	LED Panel 40W White Frame 4000K	LED Panel 40W White Frame 6000K
DIMENSIONS	1195 x 295 x 10mm		
POWER INPUT (50-60Hz AC)	40w, 220-240VAC, 50-60Hz		
POWER FACTOR, CURRENT	0.92, 1150mA		
WARM UP TIME	Instant		
COLOUR TEMPERATURE	3000K (Warm White)	4000K (Cool White)	6000K (Daylight White)
COLOUR RENDITION (CRI)	Ra>80		
LUMENS	3600lm		
CONSTRUCTION	PS diffuser/Steel Backplate/Aluminum Frame		
IP RATING	IP20		
BEAM ANGLE	120°		
LIGHT EFFICACY	90lm/w		
WORKING TEMPERATURES	-20°C to +40°C		
LIFETIME	50,000 Hours		
SWITCHING CYCLES	50,000		
ENERGY CONSUMPTION	40kWh/1000hrs		
DRIVER	Bright Source		
LAMP TYPE	2835MD		
CERTIFICATION	CE, RoHS		
WARRANTY	1 year (+ 4 years extended warranty with online registration)		



BRIGHT SOURCE



Formerly rated A+
(same quality,
new energy rating
label regulations)

