

## ALL IN ONE SWITCH LED POLO BULKHEAD

9W  
-  
14W  
-  
18W

Polo fittings with various Corridor Function, 3 Hour Emergency and Microwave Sensor options

5  
YEAR  
WARRANTY  
WITH ONLINE  
REGISTRATION



### FEATURES:

- Switchable Wattage between 9W/14W/18W:
  - i) Standard
  - ii) Microwave Sensor (detection range of 0-10 metres)
  - iii) 3 Hour Emergency
  - iv) 3 Hour Emergency and Microwave Sensor (detection range of 0-10 metres)
  - v) Corridor Function
  - vi) Corridor Function and 3 Hour Emergency
- 3 colours in 1 - easily switchable after installation
- Simple LED replacement for 2D bulkhead fittings
- Suitable for a wide range of applications, including outdoor settings
- Chrome bezel available separately - item no. 243601

### APPLICATIONS



OFFICES



EDUCATION



RETAIL



OUTDOOR

9W  
-  
14W  
-  
18W

# ALL IN ONE SWITCH LED POLO BULKHEAD

Polo fittings with various Corridor Function, 3 Hour Emergency and Microwave Sensor options


| ITEM #                       | 243540  | 243557  | 243564   | 243571   | 243588  | 243595   |
|------------------------------|---|---|--|--|---|--|
| PRODUCT NAME                 | ALL IN ONE Switch LED 2D Polo Bulkhead Standard               | ALL IN ONE Switch LED 2D Polo Bulkhead Microwave Sensor | ALL IN ONE Switch LED 2D Polo Bulkhead Corridor Function | ALL IN ONE Switch LED 2D Polo Bulkhead 3HR Emergency | ALL IN ONE Switch LED 2D Polo Bulkhead Microwave Sensor & 3HR Emergency | ALL IN ONE Switch LED 2D Polo Bulkhead Corridor Function & 3HR Emergency |
| WATTAGE                      | SWITCHABLE 9W/14W/18W (Disconnect at Mains)                   |   |  |  |   |  |
| DIMENSIONS                   | 316 x 316 x 74mm  | 316 x 316 x 74mm  | 316 x 316 x 74mm   | 316 x 316 x 74mm                                     | 316 x 316 x 74mm  | 316 x 316 x 74mm   |
| COLOUR TEMPERATURE           | SWITCHABLE 3000K/4000K/6000K                                  |   |  |  |   |  |
| COLOUR RENDITION INDEX (CRI) | Ra>80   | Ra>80   | Ra>80  | Ra>80  | Ra>80   | Ra>80  |
| LUMENS                       | 855lm/1330lm/1710lm   |   |  |  |   |  |
| IP RATING                    | IP65  | IP65  | IP65   | IP65   | IP65  | IP65   |
| IK RATING                    | IK08  | IK08  | IK08   | IK08   | IK08  | IK08   |
| BEAM ANGLE                   | 120°  | 120°  | 120°   | 120°   | 120°  | 120°   |
| CONSTRUCTION                 | POLYCARBONATE   |   |  |  |   |  |
| WORKING TEMPERATURE          | -20°C to +40°C  | -20°C to +40°C  | -20°C to +40°C   | -20°C to +40°C                                       | -20°C to +40°C  | -20°C to +40°C   |
| LIFETIME                     | 50,000hrs   | 50,000hrs   | 50,000hrs  | 50,000hrs  | 50,000hrs   | 50,000hrs  |
| SWITCH CYCLES                | 30,000  | 30,000  | 30,000   | 30,000   | 30,000  | 30,000   |
| WARRANTY                     | 1 year (+ 4 years extended warranty with online registration) |   |  |  |   |  |
| UGR RATING                   | 26.1  |   |  |  |   |  |
| LM/W                         | 95  |   |  |  |   |  |
| SDCM                         | <6  |   |  |  |   |  |
| L VALUE                      | 70  |   |  |  |   |  |
| B VALUE                      | 50  |   |  |  |   |  |
| LED CHIP BRAND               | SANAN   |   |  |  |   |  |

BRIGTH SOURCE



ACCESSORIES  
AVAILABLE  
SEPERATELY

| Part#  | Description        |
|--------|--------------------|
| 243601 | Chrome Trim        |
| 243618 | Black Eyelid Bezel |
| 243625 | Black Grill Bezel  |



Formerly rated A+  
(same quality,  
new energy rating  
label regulations)

