


LED PL-C LAMPS

6W - 15W

3CCT Switchable



FEATURES:

- Delivers 120 lumens per watt, ideal for replacing CFLs and traditional lamps.
- Adjustable color temperatures with 3CCT options.
- Operates efficiently across 100-277VAC.
- Provides uniform 360° light distribution.
- Lasts 30,000 hours with a 3-year warranty.

APPLICATIONS



COMMERCIAL



EDUCATION



HOME &
RESIDENTIAL



OFFICES



RETAIL

LED PL-C LAMPS

6W - 10W

3CCT Switchable

Part No.	247944	248002	247951	247999	247968	248019
Power Consumption	6W	6W	8W	8W	10W	10W
Description	LED PL-C G24 2 pin	LED PL-C/E G24 4 pin	LED PL-C G24 2 pin	LED PL-C/E G24 4 pin	LED PL-C G24 2 pin	LED PL-C/E 1 G24 4 pin
Product Dimensions (mm)	35 x 117	35 x 117	35 x 117	35 x 117	35 x 149	35 x 149
Product Weight (g)	60	60	60	60	66	66
Input Voltage (VAC)	100-277VAC					
Colour Temperature (k)	3000K/4000K/6000K					
CRI	≥80					
Lumen Output (lm)	720	720	960	960	1,200	1,200
CFL Replacement	10W 2 Pin G24D-1	10 4 Pin G24Q-1	13W 2 Pin G24D-1	13W 4 Pin G24Q-1	18W 2 Pin G24D-2	18W 4 Pin G24Q-2
IP Rating	IP44					
Beam Angle	360°					
Construction	Polycarbonate					
Working Temperature (°C)	-20° to +40°					
Lifetime (hrs)	30,000					
Switch Cycles	10,000 times					
Lumen Efficacy (lm/w)	120lm/W					
Certification	CE / ROHS					
Warranty	1 Year (+ 2 years extended warranty with online registration)					



G24 6W



G24 8W



G24 10W



BRIGHT SOURCE



Bright Source
248019



10
kWh/1000h



2021 No. 1095

LED PL-C LAMPS

12W - 15W

3CCT Switchable

Part No.	248088	247982	248026	247975	248033
Power Consumption	10W	12W	12W	15W	15W
Description	LED PL-C/E GX24 4 pin	LED PL-C G24 2 pin	LED PL-C/E G24 4 pin	LED PL-C G24 2 pin	LED PL-C/E G24 4 pin
Product Dimensions (mm)	35 x 149	35 x 149	35 x 149	35 x 169	35 x 169
Product Weight (g)	66	66	66	70	70
Input Voltage (VAC)	100-277VAC				
Colour Temperature (k)	3000K/4000K/6000K				
CRI	≥80				
Lumen Output (lm)	1,200	1,440	1,400	1,800	1,800
CFL Replacement	18W 4 Pin GX24Q-2	18W/26W 2 Pin G24Q-2	18W/26W 2 Pin G24Q-4	26W 2 Pin G24D-3	26W 4 Pin G24Q-3
IP Rating	IP44				
Beam Angle	360°				
Construction	Polycarbonate				
Working Temperature (°C)	-20° to +40°				
Lifetime (hrs)	30,000				
Switch Cycles	10,000 times				
Lumen Efficacy (lm/w)	120lm/W				
Certification	CE / ROHS				
Warranty	1 Year (+ 2 years extended warranty with online registration)				



10W



12W



15W



BRIGHT SOURCE



Bright Source
248033



15
kWh/1000h

