TILT ALL IN ONE LED DOWNLIGHT



New All in One Downlight with Tilt

Energy efficient LED illumination for all settings with driver on a flexible connection, great for tight spaces.



Bezel Included as Standard

White

5 additional bezel finishes are available to purchase separately:





ANTIQUE BRASS [230878]

BLACK [230816]





POLISHED CHROME BRUSHED CHROME [230830]

[230809]



[230892]





(Bezel images for illustration purpose only.)









7 Impressive Features, **1 Amazing Downlight**

- 1. Dimmable
- **2.** Fire-Resistant 30/60/90 minutes
- **3.** 3-hour emergency version available
- 4. IP65 Rated with Bezel
- **5.** Switchable Wattage 5W-8W
- **6.** 4 Colour Temperatures
- 7. Tiltable

FEATURES:

- New 5W/8W downlight added to the range
- 4CCT colour temperature changing switch (2700K, 3000K, 4000K, 6000K)
- Bezel included as standard White
- Easy to install
- Switch the bezels after installation
- Trusted, stylish design from the All in One range which includes the 8W/10W fire-rated downlight and the Tilt 8W/10W
- Tilt function allows control of the beam direction

APPLICATIONS





COMMERCIAL

RESIDENTIAL




TILT ALL IN ONE LED DOWNLIGHT

New insulation cover with easy fit Plug'n'Play connector

Part No.	230786
DESCRIPTION	5W/8W Tilt All in One Downlight 4CCT
DIMENSIONS	90 x 40mm (Excluding driver)
CUT OUT	65mm diameter
POWER CONSUMPTION	5W or 8W Selectable
INPUT VOLTAGE	AC200-240V
COLOUR TEMPERATURE	2700K (Extra Warm White) / 3000K (Warm White) / 4000K (Cool White) / 6000K (Daylight White)
COLOUR RENDITION (CRI)	Ra >80
LUMINENCE FLUX	460-540lm (5W), 720-840lm (8W)
IP RATING	IP65 (with Bezel only)
CONSTRUCTION	Aluminum / Polycarbonate
FIRE RESISTANT	BS476-21 30/60/90 minutes
BEAM ANGLE	60°
DIMMABLE	Yes
LIFETIME	54,000hrs
WORKING TEMPERATURES	-25°C to +45°C
CERTIFICATION	CE, UKCA, ROHS
WARRANTY	1 year (+ 4 years extended warranty with online registration)
EFFICACY RATING	100lm/W

LINE DRAWING





EXCELLENT PERFORMANCE FROM THE **ALL IN ONE** RANGE



8W/10W Switch 230465



8W/10W Switch Tilt 230489



4000k Cool White

6000k Daylight

COLOUR TEMPERATURE SCALE

ENERG

BRIGHT S



230786

Bright Source







