

LED PANEL LIGHT

1200x600 LOW GLARE LED PANEL - UGR<19



- Replacement for 1200x600 Modular Fittings
- Low glare UGR < 19 in compliance with EN12464-1
- Save up to 60% on energy costs
- Instant start. Flicker free
- No mercury or other hazardous materials
- 3 year warranty
- Emergency lighting version available
- Dimmable version available
- Surface mounting kit available



APPLICATIONS



Offices



Retail



Education



Commercial
Kitchens



Emergency
pack
available

LED PANEL LIGHT

1200x600 LOW GLARE LED PANEL - UGR<19

Item	223139	223146
Luminescence		
Description	LED panel 1195x595x9 72w 4000k white frame	LED panel 1195x595x9 72w 6000k white frame
Luminous flux	6500 - 6700lm	6500 - 6700lm
CCT range	3800 - 4100K	5300 - 5900K
CRI	Ra81, 5 SDCM	Ra81, 5 SDCM
Beam angle	120°	120°
Accent Lighting	No	No
Warm up time	<0.2 sec.	<0.2 sec.
Dimmable	Dimmable option available	Dimmable option available
Technical		
Power input (50-60Hz AC)	72W , 220-240V AC	72W , 220-240V AC
Power factor, current	0.9, 900MA	0.9, 900MA
Lamp type	LED	LED
Fire rated	No	No
Working temperature	-35°C ~ 50°C	-35°C ~ 50°C
Construction	Aluminium, PS	Aluminium, PS
IP rating	IP40	IP40
Efficiency		
Certification	CE, RoHS	CE, RoHS
Energy Efficiency Label	A	A
Ec (Energy consumption)	72kWh/1000h	72kWh/1000h
Lifetime	35,000 hours	35,000 hours
Warranty & LMF at EoL	3 years , 70%	3 years , 70%
Switching cycles	25,000	25,000

Emergency Pack (to be ordered separately)

Emergency pack **Item: EM3**

